AL .TIMETR% OF LAKES FOR ALTIMETER EVALUATION AND MEASUREMENT OF WATER-LEVEL VARIATION

C. S. Morris (Jet Propulsion Laboratory, California institute of Technology, Pasadena, CA, USA 91109)
S. K. Gill (National Ocean Service, NOAA, 6001 Executive Boulevard, Rockville, MD, USA 20852)

Although designed for the ocean, a satellite radar altimeter will establish lock and track over moderate-sized (> 25 km diameter) lakes. The ability to establish lock depends on the characteristics of the altimeter and the lake. Temporal changes in the altimeter-derived lake levels are a combination of real water-level variation and altimeter error. If the change in lake level is known, the temporal variation of the altimeter error can be evaluated. We have developed a technique, which we have applied to GEOSAT and TOPEX/POSEIDON Great Lakes data, that accurately estimates temporal lake level/altinleter error variation. By removing the lake-level variation, short-term effects due to orbital maneuvers, as well as long-term trends, can be detected in the altimeter system performance. The same technique can be applied to moderate-sized lakes to monitor water-level variation.

1. Charles S. Morris
MS 300-3]9
Jet Propulsion Laboratory
4800 Oak Grove Drive
Pasadena, California
USA 91109

5. Poster

6. N/A

(818) 354-8074 (818) 393-5184 (fax) email: csm@encke.j pl.nasa.gov

- 2. Session G 1 -- Altimetry of Icc and Land
- 3. Conveners: Professor C. G. Rapley Dr. Frederique Remy
- 4. N/A